



ALAMO

Performance Summary

Enhanced soil + stain resistance
Enhanced abrasion resistance
CFFA-Healthcare-201: Certified
Denim stain resistant
Fluid barrier
Bleach-solution cleanable
Enhanced fade resistance

Environmental

GREENGUARD Gold Certified
REACH Compliant
RoHS Compliant
No PFAS, fluorocarbons or perfluorinated compounds
No added flame retardants
No added antimicrobials
Does not contain formaldehyde
Formulated without Phthalates

Cleaning and Maintenance

Cleaning Code: **(W)** Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.
Bleach solutions of up to 10% may be used for more difficult stains.

Specifications

Content
Finish
Weight
Width
Roll Size

Performance Characteristics

Abrasion Resistance** CFFA-1
Adhesion CFFA-3
Break Strength CFFA-17
Tear Strength ASTM D-751-06
Seam Slippage ASTM D-751-06
Colorfastness to Light CFFA-2
Crocking CFFA-7
Fluid Barrier

Flammability*

California Technical Bulletin 117-2013, Section 1
NFPA 260
UFAC



Non-Phthalate Vinyl Surface with Polyester Backing
Advanced Soil and Stain Resistant Top Coat
26.0 oz./lin. yd. ± 1.0 oz.
54 inches
30 yards
Exceeds 100,000 double rubs - heavy duty
Warp: 3.3 lbs. min., Fill: 3.3 lbs. min.
Warp: 121 lbs. min., Fill: 72 lbs. min.
Warp: 5.6 lbs. min., Fill: 5.9 lbs. min.
Warp: 46 lbs. min., Fill: 35 lbs. min.
1000 Hours, Class 4.5
Dry: Class 4.0, Wet: Class 4.0
Inherent Fluid Barrier
Passed
Class 1
Class 1
This product is formulated without phthalates.