

Pergola

Somerset Collection

PERFORMANCE FABRIC

Performance Summary

- · Enhanced soil + stain resistance
- · Enhanced abrasion resistance
- · Fluid barrier
- · Contains an antimicrobial agent

Environmental

- · GREENGUARD Gold Certified
- NSF/ANSI 336 FACTS Silver Certified
- · LBC Red List Free
- · Non PFOA Stain Resistance
- · No added flame retardants

Cleaning and Maintenance

Cleaning Code: (W) Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.





Specifications	40 * ★□◎
Content	52% Polyester, 26% Post Industrial Recycled Polyester, 22% Post Consumer Recycled Polyester
Finish	Crypton® Non-PFOA Soil & Stain Protection
Backing	Crypton® Fluid Barrier
Weight	11.97 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Repeat	Horizontal: 4.75 inches, Vertical: 4.625 inches, directional
Roll Size	60 yards
Performance Characteristics	
Abrasion Resistance ASTM D-4157	Exceeds 50,000 double rubs - heavy duty
Break Strength ASTM D-5034	Warp: 227.0 lbs. min., Fill: 139.0 lbs. min.
Tear Strength ASTM D-2261	Warp: 35 lbs. min., Fill: 32 lbs. min.
Seam Slippage ASTM D-4034	Warp: 101 lbs. min., Fill: 60 lbs. min.
Brush Pilling ASTM D-3511	Class 3.0 min.
Colorfastness to Light AATCC-16	40 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 4.5, Wet: Class 4.5
Fluid Barrier	Crypton® Integrated Fluid Barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface.
Flammability*	
California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1