



# Posey

Somerset Collection

## PERFORMANCE FABRIC

### Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Contains an antimicrobial agent

### Environmental

- GREENGUARD Gold Certified
- NSF/ANSI 336 FACTS Silver Certified
- LBC Red List Free
- Non PFOA Stain Resistance
- No added flame retardants

### Cleaning and Maintenance

Cleaning Code: **(W)** Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

Dye lots may vary slightly.

\* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

### Specifications

Content	57% Polyester, 28% Post Industrial Recycled Polyester, 15% Post Consumer Recycled Polyester
Finish	Crypton® Non-PFOA Soil & Stain Protection
Backing	Crypton® Fluid Barrier
Weight	11.17 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Repeat	Horizontal: 2.375 inches, Vertical: 1.375 inches, directional
Roll Size	60 yards

### Performance Characteristics

Abrasion Resistance ASTM D-4157	Exceeds 75,000 double rubs - heavy duty
Break Strength ASTM D-5034	Warp: 277 lbs. min., Fill: 176 lbs. min.
Tear Strength ASTM D-2261	Warp: 22 lbs. min., Fill: 23 lbs. min.
Seam Slippage ASTM D-4034	Warp: 203 lbs. min., Fill: 75 lbs. min.
Brush Pilling ASTM D-3511	Class 4.0 min.
Colorfastness to Light AATCC-16	40 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 4.5, Wet: Class 4.5
Fluid Barrier	Crypton® Integrated Fluid Barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface.

### Flammability\*

California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1

