

Touchstone

## **Touchstone** VINYL SEATING

## **Performance Summary**

- · Enhanced soil + stain resistance
- · Enhanced abrasion resistance
- · CFFA-Healthcare-201: Certified
- · Denim stain resistant
- Fluid barrier
- · Bleach-solution cleanable
- · Enhanced fade resistance

## **Environmental**

- · GREENGUARD Certified
- · REACH Compliant
- RoHS Compliant
- · No PFAS, fluorocarbons or perfluorinated compounds
- · No added flame retardants
- · No added antimicrobials
- · Does not contain formaldehyde
- · Formulated without Phthalates

## Cleaning and Maintenance

Cleaning Code: (W-S) For water-based stains use water-based cleaners. For oil-based stains use solvent-based cleaners. We recommend using a professional cleaning service.

Bleach solutions of up to 20% may be used for more difficult stains.

Dye lots may vary slightly.

- \* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.
- \*\* Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications	<b>#</b> ♥*★□
Content	Non-Phthalate Vinyl Surface with Polyester Backing
Finish	Advanced Soil and Stain Resistant Top Coat
Backing	Polyester Fabric
Weight	32.0 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Roll Size	30 yards
Performance Characteristics	
Abrasion Resistance** CFFA-1	Exceeds 250,000 double rubs - heavy duty
Adhesion CFFA-3	Warp: 7.0 lbs. min., Fill: 7.1 lbs. min.
Break Strength CFFA-17	Warp: 106 lbs. min., Fill: 92 lbs. min.
Tear Strength CFFA-16	Warp: 6.1 lbs. min., Fill: 6.8 lbs. min.
Seam Slippage CFFA-14	Warp: 52 lbs. min., Fill: 45.5 lbs. min.
Colorfastness to Light AATCC-16	300 Hours, Class 5.0
Crocking AATCC-8	Dry: Class 4.5, Wet: Class 5.0
Fluid Barrier	Inherent Fluid Barrier
Flammability*	
California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1
MVSS 302	Passed
REDUCED ENVIRONMENTAL IMPACT	This product is formulated without phthalates.

