



Triton

Fabric Specifications

Content	76% Polyester 24% Seaqual
Finish	Crypton
Backing	Crypton
Bleach Cleanable	Yes Ratio: 90% Water / 10% Bleach Solution
Weight	18.3 oz. per linear yd
Width	54"
Roll Size	60 yards
Ends/Picks	Ends: 80 per inch Picks: 33 per inch
Repeat	H - 2.438" V - 1.0"
Directional	Yes
Railroaded	No
Made in the USA	Yes

Certifications

Greenguard Gold Certified	Yes - Crypton Technology is Greenguard Gold Certified
---------------------------	---

Recommended Cleaning

Please refer to Detailed Cleaning Instructions.

Performance Characteristics

Abrasion Resistance ASTM D4157	63,000 double rubs*
Brush Pill ASTM D3511	4
Tensile Strength ASTM D5034	Warp: 243.0 lbs. Fill: 179.0 lbs.
Tear Strength ASTM D2251	Warp: 45.0 lbs. Fill: 25.0 lbs.
Seam Slippage ASTM D4934	Warp: 102.0 lbs. Fill: 69.0 lbs.
Colorfastness to Crocking AATCC 8	Dry: 5.0 Wet: 4.5
Colorfastness to Light AATCC 16	Hours: 40.0 Class: 4.0
Flammability**	
CAL TB 117-2013	Passes
NFPA 260	Class 1
UFAC	Class 1