





Crypton Seating Fabric Bleach Cleanable FR Free – Compliant with CAL AB 2998



\*ACT® Registered Certification Marks

## **Fabric Specifications**

| Content          | 100% Polyester                                |  |
|------------------|---|--|
| Finish           | Crypton                                       |  |
| Backing          | Crypton                                       |  |
| Bleach Cleanable | Yes<br>Ratio: 90% Water / 10% Bleach Solution |  |
| Weight           | 22.7 oz. per linear yd                        |  |
| Width            | 54*   |  |
| Roll Size        | 50 yards                                      |  |
| Ends/Picks       | Ends: 160 per inch<br>Picks: 29 per inch      |  |
| Repeat           | H - N/A<br>V - 12.5 °                         |  |
| Directional      | Yes   |  |
| Railroaded       | Yes   |  |

## Additional Attributes

| Additional Attributes                                |  |
|--|--|
| Free of Added FR Chemicals / CAL<br>AB2998 Compliant | Yes  |
| Certifications                                       |  |
| Greenguard Gold Certified                            | Yes - Crypton Technology is<br>Greenguard Gold Certified |
| Recommended Cleaning                                 |  |
| Please refer to Detailed Cleaning Ins                | tructions.   |

## Performance Characteristics

| Abrasion Resistance ASTM 04157    | 69,000 double rubs*                  |
|-----------------------------------|--------------------------------------|
| Brush Pill Astmo3511              | 3                                    |
| Tensile Strength ASTM 05034       | Warp: 194.0 lbs.<br>Fill: 240.0 lbs. |
| Tear Strength ASTM 02261          | Warp: 34.0 lbs.<br>Fill: 76.0 lbs.   |
| Seam Slippage ASTM 04034          | Warp: 50.0 lbs.<br>Fill: 76.0 lbs.   |
| Colorfastness to Crocking AATCC # | Dry: 4.0<br>Wet: 3.0                 |
| Colorfastness to Light AATCC 16   | Hours: 40.0<br>Class: 4.0            |
| Flammability**                    |                                      |
| CAL TB 117-2013                   | Passes                               |
| NFPA 260                          | Class 1                              |
| UFAC                              | Class 1                              |

Although we try hard to make sure colors on our site are accurate, actual colors may vary. Please order samples prior to making a purchase.

Final determination of the suitability of this product for an application rests with the user.

- Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.
- \*\* This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

